

III. Lens Resolving Power in cycles/mm

Area-weighted average resolution: 111

Field angle:	0°	7.5°	15°	22.7°	30°	35°	40°
Radial Lines	134	159	134	134	113	95	95
Tangential Lines	134	159	134	113	113	95	80

The resolving power is obtained by photographing a series of test bars and examining the resultant image with appropriate magnification to find the spatial frequency of the finest pattern in which the bars can be counted with reasonable confidence. The series of patterns has spatial frequencies from 5 to 268 cycles/mm in a geometric series having a ratio of the 4th root of 2. Radial lines are parallel to a radius from the center of the field, and tangential lines are perpendicular to a radius.

IV. Filter Parallelism

The two surfaces of the Wild 525 filter No. 7758 accompanying this camera are within 10 seconds of being parallel. This filter was used for the calibration.

V. Shutter Calibration

Indicated Time (sec)	Rise Time (μ sec)	Fall Time (μ sec)	$\frac{1}{2}$ Width Time (ms)	Nom. Speed (sec)	Efficiency (%)
1/125	511	510	9.36	1/110	97
1/250	268	269	4.97	1/210	97
1/500	138	134	2.50	1/410	97
1/1000	69	63	1.27	1/810	97


The effective exposure times were determined with the lens at aperture f/4. The method is considered accurate within 3 percent. The technique used is described in International Standard ISO 516:1999(E).

VI. Film Platen

The platen mounted in Wild drive unit No. 5368 does not depart from a true plane by more than 13 μ m (0.0005 in).

This camera is equipped with a platen identification marker that will register "756" in the data strip area for each exposure.

VII. Principal Point and Fiducial Mark Coordinates



Positions of all points are referenced to the principal point of autocollimation (PPA) as origin. The diagram indicates the orientation of the reference points when the camera is viewed from the back, or a contact positive with the emulsion up. The data strip is to the left.

	<u>X coordinate (mm)</u>	<u>Y coordinate (mm)</u>
Indicated principal point, corner fiducials	0.020	0.010
Indicated principal point, midside fiducials	0.019	0.006
Principal point of autocollimation (PPA)	0.000	0.000
Calibrated principal point (point of symmetry)	0.001	0.004
<u>Fiducial Marks</u>		
1	-105.979	-105.991
2	106.016	106.009
3	-105.978	106.007
4	106.021	-105.991
5	-111.990	0.005
6	112.021	0.007
7	0.020	112.012
8	0.018	-111.997

VIII. Distances Between Fiducial marks

Corner fiducials (diagonals)	1-2: 299.809 mm	3-4: 299.811 mm
Lines joining these markers intersect at an angle of 89° 59' 58"		
Midside fiducials	5-6: 224.012 mm	7-8: 224.008 mm
Lines joining these markers intersect at an angle of 89° 59' 56"		
Corner fiducials (perimeter)	1-3: 211.997 mm	2-3: 211.994 mm
	1-4: 212.000 mm	2-4: 211.999 mm

The Method of measuring these distances is considered accurate within 0.003 mm

Note: For GPS applications, the nominal entrance pupil distance from the focal plane is 277mm.


IX. Stereomodel Flatness

FMC Drive Unit No: 5368

Base/Height ratio: 0.6

Platen ID: 756

Maximum angle of field tested: 40°



Stereomodel Test Point Array
(values in micrometers)

The values shown on the diagram are the average departures from flatness (at negative scale) for two computer-simulated stereo models. The values are based on comparator measurements on Agfa Avitone P3P copy film made from Kodak 2405 film exposures. These measurements are considered accurate to within 5 μm.

X. System Resolving Power on film in cycles/mm

Area-weighted average resolution: 52

Film: Type 2405

Field angle:	0°	7.5°	15°	22.7°	30°	35°	40°
Radial Lines	57	57	57	57	57	48	48
Tangential Lines	57	57	57	57	48	48	40

This aerial mapping camera calibration report supersedes the previously issued USGS Report No. OSL/3264, dated October 6, 2006.

Michael G. Benson
Remote Sensing Technologies Project Manager
Geography Discipline